

ReticleSense® Auto Multi Sensor™ (AMSR)

AMSR

○ Speed vibration, leveling and humidity measurements with all-in-one measurement device. Improve yields.



Leveling

+



Vibration

+



Humidity



Speed equipment qualification with wireless measurements.

- Collect and display acceleration, vibration, leveling and humidity data.
- Monitor humidity in reticle environments.
- Use the Auto Multi Sensor with new CyberSpectrum™ software for real-time equipment diagnostics.
- See the effects of adjustments in real-time, speeding equipment alignment and set-up.

Shorten equipment maintenance cycles with reticle-like form factor.

- 6" reticle sensor travels anywhere a reticle goes.
- Keep the process areas unexposed to the fab environment with vacuum compatible AMSR.

Lower equipment maintenance expenses and enhance process uniformity with objective and reproducible data.

- Take the human element out of adjusting your equipment with objective measurements for multiple applications in one.
- Make the right adjustments time after time.
- Receive early warning for impending equipment failures and optimize your preventative maintenance plans.

Semiconductor fabs and OEMs worldwide value the accuracy, precision and versatility of the ReticleSense AMS - The most efficient and effective wireless measurement device for leveling, vibration and humidity.




Save Time. Save Expense. Improve Yields.

CYBEROPTICS®


Features

Wireless, reticle-shaped and battery-powered	Available in 6" reticle shaped form factor
Easy-to-use software	CyberSpectrum software included CyberSpectrum: Displays real-time visual feedback. Digital readout allows more precise adjustment. Review functionality integrated; replays log file data for review and analysis.
Highly accurate - leveling	Horizontal accuracy : +/-0.03 deg within +/- 7 deg from absolute Horizontal resolution: +/-0.002deg within +/-14 deg. Reports inclination in two dimensions: x and y
Highly accurate - vibration	Reports accelerations in three directions: x, y, and z and RMS display allows quick, objective measurements. Operating range: +/- 4 G.
Relative measurements	Zero position may be set to any reference plane within the system's operating range for easy relative measurements
Humidity accuracy	+/- 2% RH
Humidity measurements	1 Relative Humidity (RH) sensor
Housing	Reticle quartz housing compatible with most all mask equipment and scanners.
Lightweight	340g (+/- 15g)
Thickness	6.35mm; standard 6" reticle format
Operating pressure	<10e-6 to 760 torr
Operating temperature	20 to 80 degrees C for extended periods. Up to 130 degrees C for shorter periods.
Battery-operation	>1 hour per charge. Inductive wireless charging and handsfree operation.
WaferSense Link	Bluetooth, 2.4 GHz, USB 1.1, dimensions 92mm x 58mm x 28mm
Operating Systems	Windows 7, 8, 10
Product components	Auto Multi Sensor measurement device, charging clean box, carrying suitcase, USB communications link module and application software
Calibration	Factory recalibration recommended annually

Dimensions



CyberSpectrum™



Contact CyberOptics today for your complimentary on-tool demonstration
+1 800.366.9131 or +1 763.542.5000 | CSsales@cyberoptics.com | www.cyberoptics.com